

# 200 gsm Satin Poster Paper



Compatible with latex, solvent, eco-solvent and UV-curable inkjet printers, this versatile, PVC-free, bright white satin poster paper is great for photo, poster and POS signage applications. With an economical price point and proprietary water-resistant, ink-receptive coating, Satin Poster Paper is an ideal choice for attractive yet economical indoor signage. The instant-dry, satin finish coating on a durable 200 gsm cellulose base helps create the most efficient workflow allowing for quick turnaround times. Compatible with most over-laminates and protective coatings for more durable indoor and short-term outdoor applications.

Features	Benefits	Applications
<ul style="list-style-type: none"><li>• Instant-dry coating</li><li>• Bright white</li><li>• Satin finish</li><li>• Cost-effective</li></ul>	<ul style="list-style-type: none"><li>• Fast dry times for lamination</li><li>• Images pop</li><li>• Low glare with direct light</li><li>• High-volume printing</li></ul>	<ul style="list-style-type: none"><li>• Retail signage</li><li>• Posters</li><li>• Exhibit graphics</li><li>• Photo enlargements</li></ul>

SPECIFICATIONS	
Material Type	Cellulose paper base
Gauge	7 mil
Applications	Posters, Indoor displays, Photo reproductions
Weight	200 gsm
Whiteness (TB-452)	98
Opacity	96%
Core Size	3" ID core
Ink Compatibility	Compatible with all inkjet printers using eco-solvent, solvent, latex, and UV-curable inks.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Water Resistance	Instant-dry and water-resistant.
Optimal Service Environment	Optimal Print Environment 70° F (21° C), 50% R.H Optimal Service Environment For printing: 60 - 80° F, 50% Relative Humidity. Handling Recommendations Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials. Rolls of film are supplied with the coated side facing out. Service Temp. Range -40 - 176° F (-40 C to 80° C).
Ink Compatibility	Latex, solvent, and eco-solvent and UV-curable inkjet printers
Light Fastness	The fading time of inkjet ink is a direct result of the inks you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Service Environment	70° F (21° C), 50% R.H
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Color	L 96.6 ± 1.0 a 1.57 ± 0.5 b* -5.07 ± 0.7
Shelf Life	1 year from the ship date when stored in proper conditions.

SKU	Size
SSPOS54200	54" x 200 ft.
SSPOS60200	60" x 200 ft.
SSPOS54300	54" x 300 ft.
SSPOS60300	60" x 300 ft.

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.